


## 40K@30Hz HDMI Point to Point Extender



### FEATURES

- Supports up to 4K@30Hz Resolution
- Supports Cat6/6A/7 Network Cables  
-1080p@60Hz Transmission Distance up to 70m  
4K@30Hz Transmission Distance up to 40m
- Zero Latency
- Supports IR Pass-Back function (20~60Hz)
- Supports HDR10 and EDID Passthrough



### DESCRIPTION

This HDMI Extender includes a transmitter unit and a receiver unit, allowing the HDMI signal to be transmitted up to 70m at 1080p resolution using a Cat6/6a/7 network cable. It adopts a point-to-point connection configuration and supports IR pass-back. It is perfect for outdoor advertising, monitor systems, home entertainment, conferencing and much more.

### SPECIFICATION

Technical	Transmitter	Receiver
HDMI compliance	1.4	
HDCP compliance	1.4	
Video bandwidth	225MHz(10.2Gbps)	
Video support	800x600, 1024x768, 1280x720, 1280x960, 1366x768, 1440x900, 1680x1050, 1920x1080, 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@24/25/30/50/60Hz, 3840x2160@24/25/30Hz	
Audio support	PCM, LPCM, DTS-HD, DTS	
InputTMDs signal	1.2Vp-p	
HDR	Support	
EDID through	Support	
IR passback	Support	
IR frequency Range (KHz)	20-60KHz	
Input	1×HDMI	1×RJ45, 1×3.5mm(IR)
Output	1×RJ45, 1×3.5mm(IR)	1×HDMI
HDMI connector	Type A, Female, 19-pin	
RJ-45 connector	RJ-45	
Mechanical	Transmitter	Receiver
Housing	Iron	
Dimensions(L×W×H mm)	75.0×60.0×16.5mm	75.0×60.0×16.5mm
Net weight	127g	127g
Power supply	5V/500mA	
Consumption	<1.5W	<1.5W
Operation temperature	-20~60℃	
Storage temperature	-30~70℃	
Relative humidity	0~90%(non-condensing)	

### ORDERING INFORMATION

Part Code	Description
32-3871	HDMI 4K@30Hz Point-to-Point