

FEATURES:



- Black PVC Sheath Material
- Available in 100m, 200m and 500m reels
- 2 Core 24 AWG
- Bare Copper Lapped Spiral
- 0.22mm² (28/0.1mm)



DESCRIPTION:

Cablenet Flexible Microphone cable is manufactured using the highest quality of materials, with 95% braided screen providing excellent screening performance whilst under flexing. This cable is available in black and in 3 different reel lengths.


SPECIFICATIONS

Conductor – Stranded Bare Copper
 Conductor Diameter (mm) – 28x0.10±0.008
 Sheath Material – Black PVC
 Overall Diameter (mm) – 6.0±0.2

ELECTRICAL PROPERTIES

Conductor DC Resistance (Ω/km) : ≤87.6
 Insulation DC Resistance (MΩ.M) : ≥3000
 Rated Temperature (°C) : -20 ~ 70 BLACK - RAL 9011
 Rated Voltage (V) : 100

TECHNICAL DRAWING



PHYSICAL PROPERTIES at 20°C

Minimum Bending Radius (mm) : 15xD
 Conductor Elongation at Break (%) : ≥15
 Sheath Tensile Strength (N/mm²) : ≥10
 Sheath Elongation at Break (%) : ≥100

ORDERING INFORMATION

Part Code	Description
39-2015	100m 2 Core 24AWG Flexible Microphone Cable XLR Black
39-2016	200m 2 Core 24AWG Flexible Microphone Cable XLR Black
39-2018	500m 2 Core 24AWG Flexible Microphone Cable XLR Black