

## OM4 50/125 CS UPC - CS UPC Fibre Lead



- OM4 CS UPC CS UPC Duplex Fibre Lead
- SENKO CS Connector (VSFF)
- Duplex Aqua
- Push-Pull Tab = Allows Quick Installation Without Tools in High-Density Space
- Uniboot Design = Allows 1 Cable To Carry 2 Fibres
  Reducing The Cable Bulk When Patching
- Individually Bagged
- Only Available in 5 Different Lengths

## **Product Features**

- IEC 60332-1-2 LSOH 3.0mm Aqua Cable
- Insertion Loss < 0.5dB</li>
- Return Loss >20dB

Dawt Cada

- Test Wavelength 850um
- Non-stocked configurations (length, colour, connectors and cable type) can be manufactured to meet specificrequirements-pleasecontactour sales team for more information.

Description

## **Product Description**

Our SENKO CS UPC - CS UPC OM4 multimode fibre optic patch leads are used for high-density fibre patching in data centres which are limited on space and help to reduce cable management issues.

The SENKO connector is a Very Small Form Factor (VSFF) Duplex Optical Connector and is manufactured using 1.25mm ceramic ferrule technology..

All assemblies are fully tested during manufacturing and are supplied with test results.

| Part Code | Description   |
|-----------|---|
| 4CSCS1    | 1m OM4 50/125 CS UPC - CS UPC Duplex Aqua LSOH Fibre Patch Lead   |
| 4CSCS2    | 2m OM4 50/125 CS UPC - CS UPC Duplex Aqua LSOH Fibre Patch Lead   |
| 4CSCS3    | 3m OM4 50/125 CS UPC - CS UPC Duplex Aqua LSOH Fibre Patch Lead   |
| 4CSCS5    | 5m OM4 50/125 CS UPC - CS UPC Duplex Aqua LSOH Fibre Patch Lead   |
| 4CSCS10   | 10m OM4 50/125 CS UPC - CS UPC Duplex Agua I SOH Fibre Patch Lead |

<sup>\*\*</sup>Other lengths are available, please contact our sales team for more information.