

FEATURES:

- RG179 Coaxial Cable
- 75ohm Stranded LSOH
- Available in 100m Reel



DESCRIPTION:

Foam-filled coaxial RG179 cable

SPECIFICATIONS:

Grey LSOH Jacket
CPR Class Eca
Inner Conductor – Stranded Tinned Copper


TECHNICAL INFORMATION:

	Dimensional Features	Material Breakdown
Inner Conductor<A>	TC0.12(+/-0.008)mm×7	Stranded tinned Copper
Insulation	1.60(+/-0.13)mm	FPE Insulation
Braid<C>	TC0.10(+/-0.008)mm×16×6	Tinned Copper Braid Shield
Sheath<D>	2.60(+/-0.15)mm	Grey LSZH Sheath

Electrical Characteristics

Max.Conductor<A> DC Resistance at 20°C (Ω/100M)	< 26.13
Min.Insulation DC Resistance at 20°C (MΩ*M)	> 200
Rated Temperature(°C)	80
Rated Voltage (V)	300
Capacitance (pF/M)	57±8
Impedance(Ω) 200 MHz	75±8
Attenuation at 20°C (-dB/100m)(±15%)	Value
10 MHz	8.45
100 MHz	24.30
200 MHz	35.60

Cable Construction



ORDERING INFORMATION:

Part Code	Description
CAB179	RG179 75ohm Solid LSOH CPR Eca Coax Cable Black 100m Reel