

Cat6 Red LSOH Network Patch Leads



- Cat6 U/UTP LSOH Network Patch Leads
- Snagless Boot
- Stranded Copper 24AWG
- PoE++ Industry Rated Full Gold IEC 60603-7 RJ45 Cat6 Connectors
- 10/100/1000 BASE-T Gigabit Ethernet
- Operating Temperature Range: -20°C to 60°C
- Storage Temperature Range Range: -20°C to 60°C
- Available in 10 Different Colours

응 Product Features

- PoE++ Industry Rated Full Gold IEC 60603-7 RJ45 Cat6 connectors
- 10/100/1000 BASE-T Gigabit Ethernet
- 24AWG Stranded Copper cable used
- 1795c Pantone Number

Product Description

Cablenet Category6 LSOH U/UTP leads are manufactured, tested and verified to the ISO 11801 Class E and ANSI/EIA/TIA standards for enhanced performance

They are constructed with IEC 60603-7 RJ45 connectors that use "Full Gold" RJ45 and a high quality PoE++ certified cable.

These are available in 13 different lengths and manufactured in 10 colours.

| Part Code | Description |
|-----------|--|
| L60-2002 | 0.2m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2003 | 0.3m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2005 | 0.5m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2010 | 1m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2015 | 1.5m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2020 | 2m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2030 | 3m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2040 | 4m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2050 | 5m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2080 | 8m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2100 | 10m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2150 | 15m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| L60-2200 | 20m Cat6 RJ45 Red U/UTP LSOH 24AWG Snagless Booted Patch Lead |
| | |

**Full Gold is a TM of Cablenet Trading Ltd for our RJ45 connectors that comply to IEE802.3bt/ISO IEC PoE Standards with 50-micron connectors