



- MPO to 4X LC (DX) QSFP Breakout Cable
- CPR Cca Cca-s1a,d0,a1 Rated Cable
- BASE-12 Method B
- OS2 Singlemode (Yellow)
- Approved For Installation Into Any Public Sector Building, Compliant With The Most Stringent Fire Regulations
- Available In a Variety of Different Lengths

Product Features

- Cca-s1a,d0,a1 rated cable
- OS2 Singlemode Yellow
- MPO to 4X LC (DX) QSFP (Harness/Breakout) cable
- Using MPO trunk and breakout cables allows much higher density cabling
- Approved for installation into any public sector building, and are compliant with the most stringent fire regulations.

Product Description

Our MPO to 4X LC (DX) QSFP Breakout CPR Cca cables (Harness/Fanout) have a MPO connector at one end and a corresponding number of LC duplex connectors at the other end (4, 6, 8 or 12). Other connectors are used, but LC is by far the most popular option.

In a data centre environment with ever-increasing bandwidth and network connections, conventional duplex fibre leads are unable to meet these increased demands.

This is where MPO cables are the perfect solution. A single MPO connector can house up to 24 fibres in a form-factor that is very similar in size to a duplex LC connector.

Part Code	Description
MPO-12BO9LC1	1m OS2 BASE-12 MPO (F) TO 4X LC (DX) QSFP Breakout Yellow CPR Cca Cable Method B
MPO-12BO9LC2	2m OS2 BASE-12 MPO (F) TO 4X LC (DX) QSFP Breakout Yellow CPR Cca Cable Method B
MPO-12BO9LC3	3m OS2 BASE-12 MPO (F) TO 4X LC (DX) QSFP Breakout Yellow CPR Cca Cable Method B
MPO-12BO9LC5	5m OS2 BASE-12 MPO (F) TO 4X LC (DX) QSFP Breakout Yellow CPR Cca Cable Method B
MPO-12BO9LC10	10m OS2 BASE-12 MPO (F) TO 4X LC (DX) QSFP Breakout Yellow CPR Cca Cable Method B

**Other lengths are available, please contact our sales team for more information