

AV & SECURITY

High Definition Coax Cable

FEATURES:

- High Definition Coax Cable
- Black LSOH Jacket
- 100m Reel





DESCRIPTION:


The VFX2000BK cable is designed to work in a variety of applications from low frequency audio up to high-bandwidth installations like long runs of SDI which makes this the perfect solution for high quality BNC video cables. Supplied as 100m reel.

SPECIFICATIONS:

Inner Conductor – Solid Copper Insulation - FPE Shield – Aluminum Foil Black LSOH Jacket CPR Class Eca

TECHNICAL INFORMATION:

Conductor Diameter (mm)	1.02 <u>+</u> 0.01
Dielectric Material	Foam PE
Dielectric Diameter (mm)	4.57 <u>+</u> 0.15
Shield Coverage	≥100%
Braiding Coverage	\geq 95%(24x8x0.12+0.008)
Sheath Diameter (mm)	6.9 <u>+</u> 0.2



Conductor DC Resistance	<u>≤</u> 22.0
Insulation DC Resistance at 20°C	≥5000
Rated Temperature (°C)	-20~80
Rated Voltage (V)	300
Impedance @200MHz	75 <u>+</u> 3
Capacitance (pF/m)	53 <u>+</u> 3
VP (%)	85
Return Loss (dB)	$5 - 3000 \ge 20$
	$3000 - 6000 \ge 15$

Physical Properties at 20°C	
Minimum Bending Radius (mm)	15xD
Conductor Elongation at Break (%)	≥15
Sheath Tensile Strength (N/mm²)	<u>≥</u> 9
Sheath Elongation at Break (%)	≥100

ORDERING INFORMATION:

Part Code	Description
VFX2000BK	High Definition LSOH CPR Eca Coax Cable Black 100m Reel

Tel: 01276 405 300 Email: sales@cablenet.co.uk Web: www.cablenet.co.uk