



NO.	REV	DESCRIPTION	DATE

FNAME

A

A

B

B

C

C

NOTE:
 1. 100% OPEN, DISLOCATION TEST;
 2. ON-RESISTANCE MAX 3.0 Ω ;
 3. INSULATION RESISTANCE MIN 5M Ω .

cable structure

PIN OUT

P1	P2
1	1 VCC
2	2 D-
3	3 D+
4	5 GND
5	S SHIELD

6	8pin shell	Rustless iron SUS304 L13.8*T0.25mm	1	
5	8pin plug	White 45P PVC	1	White
4	8PIN connector	Lightning C89 Nickel plated	1	Nickel
3	USB A plug	White 45P PVC	1	White
2	USB A connector	USB AM Nickel plated	1	Nickel
1	cable	11/0.08TC*2C+65/0.08TC+AL, OD3.5mm White PVC , L=2.0M		White
NO.	Title	Description	Q'ty	Remark

		USB AM - 8PIN MFI CABLE 2.0M			
		PART NO. 32-0302		customer P/N	
				COMP P/N	
Draw	WZC	CONSUMER			
Check		DATE	2021.05.20	REV.	A
APP.		PAGE 1 of 1	UNIT	mm	SCALE 1:1

1

2

3

4

5

6

D