

| NO. | REV | DESCRIPTION | DATE |
|-----|-----|-------------|------|
| | | | |

2000±20

6.7±0.2

P1
10.5±0.2

B1 A1
B12 A12

6.65±0.1

26.0±0.3

②③④


①

6.7±0.2

A1 B1
A12 B12

P2
10.5±0.2

3.8±0.2



Conductor: 65/0.08BC
red/black

Conductor: 10/0.10BC
white/green/yellow

Jacket: White PVC, OD 3.8mm

cable structure

P1 (USB Type-C)

P2 (USB Type-C)

A4, A9

Vcc /Red

A4, A9

B4, B9

CC /Yellow

B4, B9

A5

D- /White

A5

A6

D+ /Green

A6

A1, A12

GND /Black

A1, A12

B1, B12

B1, B12

C=10nF

wiring diagram

NOTE:

1. 100% OPEN, DISLOCATION TEST;
2. ON-RESISTANCE MAX 3.0 Ω ;
3. INSULATION RESISTANCE MIN 5M Ω .

| NO. | Title | Description | Q'ty | Remark |
|-----|---------------|---|------|--------|
| 3 | USB plug | 45P PVC White | 2 | white |
| 2 | USB connector | USB Type-C Nickel plated With PCB C=10nF | 2 | Nickel |
| 1 | cable | (10/0.1BC)*3C+(65/0.08BC)*2C, White PVC Jacket, OD3.8MM, L=2.0M | | white |

| Draw | | WZC | | CONSUMER | | DATE | | 2021.05.20 | | REV. | | A | |
|------|--|-------------|--|----------|--|------|--|------------|--|------|--|---|--|
| APP. | | PAGE 1 of 1 | | UNIT | | mm | | SCALE | | 1:1 | | | |

TYPE C-TYPE C CABLE 2.0M

PART NO.

40-4072W

customer P/N

COMP P/N

