



NOTE:  
 1. 100% OPEN, DISLOCATION TEST;  
 2. ON-RESISTANCE MAX 3.0Ω;  
 3. INSULATION RESISTANCE MIN 5MΩ.

|     |                 |  |      |        |
|-----|-----------------|--|------|--------|
| 6   | 8pin shell      | Rustless iron SUS304 L13.8*T0.25mm                       | 1    |        |
| 5   | 8pin plug       | White 45P PVC  | 1    | White  |
| 4   | 8PIN connector  | Lightning C94 Nickel plated                              | 1    | Nickel |
| 3   | USB C plug      | White 45P PVC  | 1    | White  |
| 2   | USB C connector | USB TYPE C Nickel plated                                 | 1    | Nickel |
| 1   | cable           | 11/0.08TC*3C+65/0.08TC+AL, OD3.5mm<br>White PVC , L=2.0M |      | White  |
| NO. | Title           | Description  | Q'ty | Remark |

|       |     |                               |            |              |           |
|-------|-----|-------------------------------|------------|--------------|-----------|
|       |     | USB TYPE C TO 8PIN CABLE 2.0M |            |              |           |
|       |     | PART NO.                      | 40-4077    | customer P/N |           |
|       |     |                               |            | COMP P/N     |           |
| Draw  | WZC | CONSUMER                      |            |              |           |
| Check |     | DATE                          | 2021.05.20 | REV.         | A         |
| APP.  |     | PAGE 1 of 1                   | UNIT       | mm           | SCALE 1:1 |