



Type C	Core color	Type C
A1,B1,A12,B12	Ground	A1,B1,A12,B12
A4,B4,A9,B9 (VBUS)	Red	A4,B4,A9,B9 (VBUS)
A5 (CC)	Yellow	A5 (CC)
B5 (Vconn)	Cypress 2103(E-mark)	B5 (Vconn)
A6 (UTP D+)	Green	A6 (UTP D+)
A7 (UTP D-)	White	A7 (UTP D-)
A2 (SSTXp1)	Coax Yellow	B11 (SSRXp1)
A3 (SSTXn1)	Coax Purple	B10 (SSRXn1)
B11 (SSRXp1)	Coax Brown	A2 (SSTXp1)
B10 (SSRXn1)	Coax Orange	A3 (SSTXn1)
B2 (SSTXp2)	Coax Black	A11 (SSRXp2)
B3 (SSTXn2)	Coax Blue	A10 (SSRXn2)
A11 (SSRXp2)	Coax White	B2 (SSTXp2)
A10 (SSRXn2)	Coax Green	B3 (SSTXn2)
A8 (SBU1)	Orange	B8 (SBU2)
B8 (SBU2)	Purple	A8 (SBU1)
Shell	Braiding	Shell

④	Outer Molding	TPE	2
③	Inner Molding	TPE	2
②	Type C Connector	Pin: Gold plated Shell: Nickel plated	2
①	Cable	Ø4.8(30AWGx8coax+32AWGx4c+32AWGX1P+25AWGX2C+FABD)	1
NO.	Parts Name	Specification	Q`TY

APPROVED	CHECKED	DRAWN	CUSTOMER:	----
Mark	David	John	ITEM NO.	40-4421
			DRAW NO.	----
			UNIT	mm
			SCALE	NONE

DESCRIPTION:
USB4 Gen3 240W Cable

