


Side A



24F MPO Elite Connector Female

24F OS2 Micro CPR Cable

Breakout Module


Side B

2mm Duplex Furcation Tubing

LC Duplex Connector

500 ± 50

KEY




Position	1	2	3	4	5	6	7	8	9	10	11	12
Fiber Color	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Purple	Pink	Aqua
Position	13	14	15	16	17	18	19	20	21	22	23	24
Fiber Color	Blue/T	Orange/T	Green/T	Brown/T	Grey/T	White/T	Red/T	Black/T	Yellow/T	Purple/T	Pink/T	Aqua/T

Side A

/T=With Tracer

Optical Performance Index


Parameter	Type	MPO/PC	LC/UPC
Wavelength		850nm&1300nm	850nm&1300nm
IL		≤0.35dB	≤0.3dB
RL		≥20dB	≥20dB



Outer jacket
Kevlar
Colored fiber

LENGTH TOLERANCE:

LENGTH(L)	TOLERANCE
< 1M	+50mm/-0
< 1M≤10M	+150mm/-0
< 10M≤30M	+150mm/-0
≥30M	+1%mm/-0



Designed	wang	2022.09.07
Checked	sun	2022.09.07
Approved	sun	2022.09.07
Units	mm	
Version	A0	
Scale		

sheet 1 of 1

MPO-24BO9LC5

