




Side A



Side B

24F MPO Connector Female

24F MM Micro Cca Cable



Position	1	2	3	4	5	6	7	8	9	10	11	12
Fiber Color	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Purple	Pink	Aqua
Position	13	14	15	16	17	18	19	20	21	22	23	24
Fiber Color	Blue/T	Orange/T	Green/T	Brown/T	Grey/T	White/T	Red/T	Black/T	Yellow/T	Purple/T	Pink/T	Aqua/T

Position	1	2	3	4	5	6	7	8	9	10	11	12
Fiber Color	Aqua	Pink	Purple	Yellow	Black	Red	White	Grey	Brown	Green	Orange	Blue
Position	13	14	15	16	17	18	19	20	21	22	23	24
Fiber Color	Aqua/T	Pink/T	Purple/T	Yellow/T	Black/T	Red/T	White/T	Grey/T	Brown/T	Green/T	Orange/T	Blue/T


Side A

Side B

/T=With Tracer


Optical Performance Index

Type	MTP/PC
Wavelength	850nm&1300nm
IL	≤0.35dB
RL	≥20dB



LENGTH TOLERANCE:

LENGTH(L)	TOLERANCE
<1M	+50mm/-0
<1M≤10M	+150mm/-0
<10M≤30M	+150mm/-0
≥30M	+1%mm/-0



Units	mm
Version	A0
Scale	

Designed	wang	2022.09.07
Checked	sun	2022.09.07
Approved	sun	2022.09.07

MPO-24TC4MPO5



sheet 1 of 1